

Scrubber-dryer range - TBL8572T (100ah / 150ah)

| TBL8572T (100AH / 150AH) | |
|---------------------------------|--|
| BRUSH WEIGHT | 13kg / 28kg |
| BRUSH DIAMETER | 720mm (2 X 370mm) |
| BRUSH PRESSURE | 8.2 / 17.5 g/cm ² |
| PAD DIAMETER | 700mm (2 X 360mm) |
| PAD PRESSURE | 6.9 / 14.8 g/cm ² |
| CLEANING AREA | 2592m ² /HOUR @ 3.6 kph |
| BRUSH MOTOR POWER | 600W |
| BRUSH SPEED | 150 rpm |
| VAC MOTOR MAX. POWER | 400W |
| VAC MOTOR - SUCTION @ SQUEEGEE | 120 mbar |
| VAC MOTOR - AIRFLOW @ SQUEEGEE | 24 l/sec |
| WATER CAPACITY | 85L |
| WATER FLOW RATE | 0 - 3l/min |
| TRANSAXLE POWER | 400W |
| DRIVE SPEED | 0 - 4.2 kph |
| MAX GRADIENT (FULL TOP TANK) | 6% OR 3.5° |
| GROSS WEIGHT (I.E. WITH LIQUID) | 100Ah : 289.11kg 150Ah: 299.91kg |
| NETT WEIGHT (I.E. NO LIQUID) | 100Ah : 204.11kg 150Ah : 214.91kg |
| POWER SOURCE | 2 Battery: LFP battery (Li-ion) 25.6 V (2x 50Ah) 2560Wh 3 Battery: LFP battery (Li-ion) 25.6 V (3x 50Ah) 3840Wh |
| RUN TIME (BATTERY LIFE) | 100Ah : 3hr (MAX) 150Ah: 4hr 30 mins (MAX) |
| RECHARGING TIME | 100Ah : 5 hrs 150Ah: 7 hrs 30 mins |
| INTERNAL CHARGER INPUT | 600W |
| INTERNAL CHARGER OUTPUT | 20A DC |
| HEIGHT | 1144mm |
| LENGTH | 1513mm |
| WIDTH | 762mm (948mm) |
| SQUEEGEE WIDTH | 948mm |
| SOUND PRESSURE LEVEL | Lpa ≤ 70 dB(A) |
| VIBRATION LEVEL | HAV ≤ 0.54 m/s ² HAV ≤ 1.77 ft/s ² |
| WATER INGRESS PROTECTION | IPX4 |

TBL8572T/100: 916209 / EAN: 5028965850664

TBL8572T/150: 915021 / EAN: 5028965838440




NU-ASSIST APPLICATION


With the Nu-Assist App on hand, you and your team have 24/7 access to multilingual training, troubleshooting and maintenance content from any device, increasing cleaning productivity across the board.



INCLUDED ACCESSORIES



2 x 903449 - 370MM POLYSCRUB SCRUBBING BRUSH



903853 - 750 TWINTEC ALUMINIUM FLOOR TOOL (38MM HOSE, RED TRIM, SERILOR BLADES)



220386 - UK TYPE CHARGING LEAD