

SOC-E-IS

Intrinsicly Safe Conventional Smoke Detector

Features

- ▶ Removable, High Performance chamber
- ▶ Automatic Sensitivity Window Verification (ASWW) – Drift Compensation Technology
- ▶ Remote Indicator output
- ▶ Wide voltage range (9.5 ~ 30 VDC)
- ▶ Low profile design with one piece outer cover
- ▶ Single fire LED - 360° viewing
- ▶ ATEX Classification to:
Ex ia IIC T5 Ga (-20°C ≤ Ta ≤ +55°C)
- ▶ Suitable for installation in areas at Category 1 (inc all lower categories)
- ▶ Approved by LPCB, VdS and DNV-GL



Description

The SOC-E-IS is a Photoelectric Smoke Detector, which is fully compatible with the majority of existing Conventional systems. The SOC-E-IS incorporates Hochiki's unique High Performance photoelectric smoke chamber removing the need to use Ionisation Detectors in the majority of applications.

'ASWW' Drift Compensation technology is incorporated to ensure the Detector

is operating at its optimum sensitivity and therefore reducing potential false alarms. If the contamination limit is exceeded then the integral red LED will flash once every three seconds to give a visual warning. The smoke chamber is easily removed or replaced for cleaning and utilises a unique baffle design which allows smoke to enter the chamber whilst keeping out ambient light.

Specification

Ordering codes	SOC-E-IS - Ivory / SOC-E-IS(WHT) - White
Compatible Base	YBN-R/4(IS)
Operating Voltage	12 - 30 VDC
Quiescent Current (typ)	35 µA
Maximum Current In Alarm	40 mA
Out of Sensitivity Current (RED flashing LED)	120 µA
Remote Indicator Drive	20 mA (max)
Operating Temperature Range	-20 °C to + 55 °C
Storage Temperature Range	-30 °C to + 60 °C
Maximum Humidity	95% RH - Non condensing (at 40 °C)
Ingress Protection Rating	IP42
Colour / Case Material	Ivory or White / ABS
Weight (g) / Dimensions (mm)	106 / ø 100 x H 48
Approvals	LPCB VdS Bassefa 19ATEX0143X IECEX BAS 19.0122X DNV-GL
ATEX Certification	Certificate Number: Baseefa19ATEX0143X EC Intrinsic Safety to classification Ex ia IIC T5 Ga (-20°C ≤ Ta ≤ +55°C)
LPCB Certification	EN 54-7:2000 + A1:2002 + A2:2006
Other Certification	VdS (G220019), DNV-GL, SIL2*, EAC*, Intertek



For further information visit our website. Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.

