

ACD-EN

Addressable Multi-Sensor with CO Detection

Features

- ▶ Low profile
- ▶ Heat ,Optical and CO sensing elements
- CO Alarm (COHb) facility
- ▶ Programmable fire threshold level
- ▶ RI & LED controllable separately if required*2
- ▶ 2 colour LED (Polling: Green, Fire: RED)
- > 24 EN approved modes of operation
- \blacktriangleright Designed for up to 10 year's CO cell life*1
- > Fully monitored CO cell including end of life warning on the panel
- ▶ 3 year warranty period.



Description

An addressable loop-powered multi-sensor, with smoke, heat and CO sensing elements. The unit offers 24 different modes of operation*2 and seamlessly matches the other sensors in the ESP Range. The CO sensing element can

be used to detect smoke as well as life-threatening CO levels (acting as a CO alarm).

Note: Control Panel compatibility required

| Specification | | |
|-------------------------------|---|----------------------------|
| Ordering Code | ACD-EN - Ivory ACD-EN(WHT) - White | |
| Operating Voltage | 17 – 41 VDC | |
| Loop Pulse Voltage | 7 - 9 VDC | |
| Current Consumption | Quiescent | 410 μA (typ)* ³ |
| | LED Current | 9.1 mA* ³ |
| | Surge Current | 40 mA (for 50 ms) |
| Operating Temperature Range*3 | - 10 °C to + 50 °C | |
| Relative Humidity | <95% RH (at 40 °C) <80% RH (at 50 °C) | |
| Storage Temperature Range | - 20 °C to + 50 °C | |
| Colour / Case Material | Ivory or White / Polycarbonate (Outer Cover) / PC/PS-GF (terminal plate) | |
| Weight without Base (g) | 105 | |
| Diameter (mm) / Height (mm) | ø 100 / 45 (without base) | |
| Compatible Bases | YBN-R/3, YBO-R/SCI, YBN-R/3(SCI)*5, YBO-BS, YBO-BS2, YBO-BS2(SCI)*5, YBO-BSB, YBO-BSB2, YBO-BSB2, YBV-R/4*5 | |
| Approvals | EN 54-5:2000 + A1:2002 / EN 54-7:2000 +A1:2002 + A2:2006 / EN 54-26: 2015 EN 54-29: 2015 / EN 54-30: 2015 / EN 54-31: 2015 / CEA 4021:2003 | |

Note: This sensor does not support sleep mode.

- *1 Dependent on environmental conditions and in accordance with our installation guidelines.
- *2 Panel compatibility dependant.
- *3 Currents are cumulative.
- *4 Operating temperature complies with standard sensitivity.

For further information visit our website.

*5 Integral SCI functionality











