

# TBL4045

Fast Charge, Long Life, Flexible Power





# TBL4045

Powered by NX1K, with 40L capacity and 450mm scrub width, user-friendly controls and on-board charging system. The 4045 is the ultimate in mid-sized scrubber versatility and performance.

## POWERFUL Cleaning Results

NX1K Battery Range powers commercial grade TwinFlo vacuum and brush motor for unrivaled cleaning performance in the most demanding environments.

## CLEAN, DRY & SAFE Floors in Minutes

Consistent, quick and high-quality cleaning results, wherever they're needed.

## FAST & FLEXIBLE Charging

Latest lithium phosphate technology provides fast charging with complete flexibility, with no impact on battery health.

## USER FRIENDLY Features

Incorporating user-friendly, colour-coded controls for ease of use.

## STAY CLEANING for Longer

With 40L capacity and up to 3 hours 10 minutes runtime, the TBL4045 keeps you cleaning for longer.

## Nu-Assist

With the Nu-Assist App on hand, you and your team have 24/7 access to multilingual training, troubleshooting and maintenance content from any device, increasing cleaning productivity across the board.

## Next Generation Lithium Power


4x Longer Lasting than Lead Batteries\*

Advanced & Safe Lithium Phosphate Technology

Flexible Charging

4000 Charge Cycles

Extended Long-Life Power†



## Accessories and Replacement Parts

A comprehensive range of accessories and replacement parts are available to achieve professional results, whatever the challenge.



## Specifications

Model	Batteries	Runtime	Recharge	Capacity	Deck	Brush	Pad	Brush Speed	Dimensions (WxLxH)
TBL4045	x1	1hr 40mins	2hr 30mins	40L	450mm	450mm	400mm	140 RPM	805x1155x1160mm
	x2	3hrs 10mins	5hrs						

\*Any comparisons used are based on typical usage scenarios, results may differ. Performance comparisons use equivalent GelTec models.

† Standard battery warranty is 5 years, with up to 8 years battery warranty available subject to terms and market agreement. Please contact Numatic for more information.

# Numatic

numatic.com

©Numatic International Limited 2023. Specification subject to change without prior notice.

