



HOCHIKI FirePro.

FNX-3000/S/T/TS

Condensed Aerosol Generators



Technical Data

Mass of FPC (Aerosol Generating Solid Compound)	3000 g			
Generators gross weight	Weight	Tolerance		
	16300 g	± 5%		
Activation mode/s	Electrically			
Value of activation	1.5 V DC , 0.8 A			
FPC activation device	Heating elements with 1.6-3.6 Ω Resistance			
Activation line supervision current (Max)	5 mA			
Aerosol discharge time	Min.	Max		
	15 seconds	20 seconds		
Number of discharge outlet	1			
Generator dimension	Height	Width	Length	
	185 mm	300 mm	300 mm	
Self-activation temperature of FPC	300° C			
Classes of Fire (NFPA 2010)	A	B	C	D
	√	√	√	NO
Generator Coverage Constraints	Min ht: 0.45 m		Max area: 32.03 m ²	
Maximum height of installation	3.5 m			
Minimum clearance (mm)	From persons	From combustible material	From Generator's Casing	
	2000 mm	600 mm	6.4 mm	
Environmental parameters	ODP¹	GWP²	ALT³	
	Zero	Zero	Negligible ⁴	
Technical Parameters	Electrical conductivity	Corrosion	Oxygen depletion After discharge	
	Nil up to 75KV	Negligible ⁴	Negligible ⁴	
Note	1	ODP: Ozone Depletion Potential	3	ALT: Atmospheric Life Time
	2	GWP: Global Warming Potential	4	Within the parameters for use

HOCHIKI ASIA PACIFIC PTE. LTD.

ADD: 82 UBI Ave 4 #06-02 Edward Boustead Centre, Singapore 408832 | TEL: 65-6841-9728 | URL : www.hochikiasiapacific.com

08/2024

Specifications subject to change without notice.