



# Discharge Hose

SG-227EA / SG-FK5112 Fire Extinguishing System



DN38 & DN50 Discharge Hose



DN50 Extended Elbow Discharge Hose



DN80 Discharge Hose

## Specification

General Description	For carrying agent from cylinder to outlet
Certification No.	EX28621
Material	Synthetic Rubber / Stainless Steel

Part Number	SG-SR-010 -38MM	SG-SR-012 -38MM	SG-SR-010- 50MM	SG-SR-012 -50MM	SG-SR-011-50MM (Extended Elbow)	SG-SR-012- 80MM
Name	DN 38		DN 50		DN 50	DN80
Material	Synthetic Rubber Hose with high tensile steel wire reinforcement					Hose: Stainless Steel Coupling: Ductile Iron
	Single Braided	Double Braided	Single Braided	Double Braided	Single Braided	
Max. Working Pressure	50 bar	90 bar	40 bar	80 bar	40 bar	28 bar
Temperature Range	-10 °C to 60 °C					
Length from Elbow Inlet	465 mm		520 mm		520 mm	650 mm
Elbow Inlet	1-7/8" – 12 UNJ		2-1/2" – 12 UNJ		2-1/2" – 12 UNJ	3" Groove Connection
Outlet	2" BSP		2-1/2" BSP		2-1/2" BSP	3" Groove Connection
Equivalent Length (m)	4.0		4.4		4.4	-

Note: All equivalent lengths given in Schedule 40, black pipe.

HOCHIKI ASIA PACIFIC PTE. LTD.

82 UBI Ave 4 #06-02

Edward Boustead Centre, Singapore 408832 TEL: 65-6841-9728 |

FAX: 65-6841-9781 URL : www.hochikiasiapacific.com

02/2023



Approval / Compliance:

Component of FM & UL Listed SG Fire Systems

Specifications subject to change without notice.