


# CCP-E

## Conventional Manual Call Point

### Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm<sup>2</sup> solid conductor
- ▶ Other colours available on request
- ▶ Approved by LPCB (red variant only- other colours not EN54 approved)



### Description

The CCP-E is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals. The unit can support either a 'Frangible Glass' element or a 'Non Frangible

Plastic' element.

**IMPORTANT NOTE:** If changing the element from Glass to Flexi, please confirm the operation by pressing the resettable element.

### Specification

Ordering codes	CCP-E - Red / CCP-EB - Blue / CCP-EO - Orange / CCP-EY - Yellow			
Nominal operating resistance	470 Ω			
Maximum contact resistance (R)	200 Ω			
IP rating	IP24			
Operating / Storage temperature range	-10 °C to + 55 °C			
Maximum Humidity	95% RH - non-condensing (at 40°C)			
Colour / Case Material	Red, Blue, Orange or Yellow / ABS			
Weight (g) / Diameter (mm) / Height (mm)	110 / W 89 x H 93 x D 27.5 (Flush mount)			
	161 / W 89 x H 93 x D 59.5 (Flush mount)			
Accessories	Frangible element	KAC/G/HE	Non-frangible element	KAC/EWS/HE



For further information visit our website. Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.