TBL4055T Fast Charge, Long Life, Flexible Power



TBL4055T

The TBL4055T traction scrubber dryer is the ultimate in mid-sized machine in versatility and performance. Commercial grade TwinFlo vacuum, and brush motor provide unrivalled cleaning performance in the most demanding environments.

The 4055T Traction offers effortless cleaning from the powerful traction unit. Traction is essential where inclines are present. Powered by the latest lithium phosphate technology, NX1K. Providing fast charging with complete flexibility, with no impact on battery health. A huge 40L capacity, 100rpm brush speed and 550mm scrub width, user-friendly controls and on-board charging system providing powerful cleaning results.

POWERFUL Cleaning Results

Unrivalled cleaning performance in the most demanding environments.

CLEAN, DRY & SAFE Floors in Minutes Consistent, quick and high-quality cleaning results,

wherever they're needed.

FAST & FLEXIBLE Charging NX1K technology provides fast and flexible charging.

USER FRIENDLY Features Incorporating user-friendly, colour-coded controls for ease of use.

EFFORTLESS Cleaning Effortless cleaning with powerful traction unit.

Mu-Jrack Insights

Built-in intelligent fleet management telemetry system, Nu-Track, provides in-depth insights, lowering costs and increasing productivity across your fleet

NU-Assist

With the Nu-Assist App on hand, you and your team have 24/7 access to multilingual training, troubleshooting and maintenance content from any device, increasing cleaning productivity across the board.

Next Generation Lithium Power

4x Longer Lasting than Lead Batteries Advanced & Safe Lithium Phosphate Technology **Flexible Charging** 4000 Charge Cycles 3 Years Warranty[†]



Accessories and Replacement Parts

A comprehensive range of accessories and replacement parts are available to achieve professional results, whatever the challenge.

Specifications

	1.00				Act in the				
Model	Batteries	Runtime	Recharge	Capacity	Deck	Brush	Pad	Brush Speed	Dimensions (WxL>
TBL4055T	x1	1hr 33mins	2hrs 30mins	40L	550mm	550mm	508mm	140 RPM	948x1200x1160n
	x2	3hrs 4mins	5hrs						

*Any comparisons used are based on typical usage scenarios, results may differ. Performance comparisons use equivalent GelTec models.



[†]3 Years warranty subject to terms and market availability, please contact Numatic for more information.

ish Speed	Dimensions (WxLxH)				
40 RPM	948x1200x1160mm				

*Nu-Track subject to market/model availability



ITTEL .

numatic.com

©Numatic International Limited 2024. Specification subject to change without prior notice