

Hazardous Class


Name	HZC.390L-2 HZC.390S-2
Reference	910218
EAN code HZ390L-2	05028965793732
Reference HZ390S-2	910217
EAN code	05028965793749
Power supply	
Power supply type	230v AC 50/60Hz
Rated Motor Power	960W
Protection class	Class I
Airflow Motor only	48 L/sec
Suction	2500mm H ₂ O
Max Flow Rate	31.8 L/sec / 114.5 m ³ /h
MAX Under Pressure	230 (hPa)
Low Flow Operation	< 20L/sec
Sound Pressure (LpA)	74.48 + dB (A)
Uncertainty (KpA)	0.5 dB
Cable length	10m
Cleaning Range	26.8m
Cable Type	HO5VV-F
NUPLUG system	Yes
Capacity / Weight Size	
Drum Capacity (DRY)	13.0L
Weight (Ready to Work)	13.0kg / 12.2kg
Packed Weight	15.08kg / 13.93kg
Width	450mm
Length	400mm
Height	1010mm / 600mm
Filtration	
Hazardous Class (EN60335-2-69)	H Class
Filter Type (901649 Cartridge)	H13 (EN1822)
HZC Disposable Cartridge	909007 to Re-order
Kit AA16 (2.2p) 909539	
915907 32mm Parallel hose (BoFlex) 2.2m	
602159 38/32mm Adaptor	
601141 32mm Double Taper Adaptor	
601144 65mm Soft Dusting Brush	
601917 280mm Stainless Steel Gulper/Scraper Tool	
611142 32mm Crevice Tool	
604151 Air Diffuser	
602161 152mm Rubber Brush with Soft Bristles	



DRY VACUUM

Designed, engineered and built with the tradesman in mind, the HZC390 offers a safe and convenient solution for those whose work brings them into frequent contact with hazardous dusts and materials. Equipped with a sealed and disposable HEPA H13 filter cartridge, all dust is safely contained, meaning users can change the filter as and when they need to.

**H-Class Compliant
Unparalleled Safety
Compact & Ready
Take Control
All-Terrain**



H CLASS

H
CLASS

Suitable for:-
Asbestos.

These are suggested possible uses. Check local H&S/Statutory regulations for the type of machine required for a specific use or dust type in your area /country as regulations may differ.



DRY

Specification subject to change without prior notice